

# Rock wool lagging rope

GB / 2.5 / Rev.5

# **BOURRELET ODICE**





#### Product description

The **BOURRELET ODICE** lagging rope consists of a braid of rock wool (125 kg/m<sup>3</sup>) tighten with a polyamide cord. The rock fibre is used as a thermal and acoustic insulation and for its fire resistance properties.

The **BOURRELET ODICE** is mainly used as a fire resistant backer material for sealing concrete blocks or as filler for all kind of expansion joints in a building.

Installation is facilitated by the high flexibility of the fibre which allows placing it into even the narrowest gaps. Delivered in roll, it is easy to cut on site.

Depending on the fire resistant rating and the required finish, it is recommended to use **ACRYLODICE F** or **FIRESTOP 700** sealant (refer to the technical data sheets).

#### **Features**

- **BOURRELET ODICE** is resistant to high temperatures and is stable at temperatures up to 780°C (melting point > 1000°C).
- The product is free from asbestos and ceramic fibres.
- Easy to install (thanks to its high flexibility) and to prepare (can be cut with a cutter).
- High thermal insulation properties.

## Typical applications

- Various fire resistant seals in buildings.
- Fire resistant expansion joints.
- Thermal insulation for industrial piping.

### **Product range**

Diameter	Roll length
Ø 20 mm	30 metres
Ø 30 mm	45 metres

Other sections on request, please contact us.

#### Storage

Store in a dry, well-ventilated area. Avoid exposure to draughts.

#### Health and safety measures

Observe usual workplace health and safety rules. Refer to the safety data sheet.



VISIBLE JOINT

IMPORTANT: while the descriptions, designs, data and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding products described or designs, data or information set forth, or that the products, designs, data or information may be used without infringing the intellectual property rights of others. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sale. Further, you expressly understand and agree that the descriptions, designs, data and information furnished by ODICE hereunder are given free of charge and ODICE assumes no obligation or liability for the description, data and information given or results obtained, all such being given and accepted at your risk.



**ODICE S.A.S.** Passive Fire Protection Z.A.E Les Dix Muids - Rue Lavoisier - 59770 Marly - France Tél. +33 (0)3 27 19 32 32 - Fax : +33 (0)3 27 21 06 26 Email : info@odice.com - www.odice.com